

# Pocket-size PAR logger

# DEFI2-L

ISO9001



JQA-0950


Photosynthetically Active Radiation (PAR) sensor



- Non-opening infrared communication
- Flashing LED light for activation check
- USB connection to PC (via interface unit)
- Powered by commercial AAA batteries
- Data logging: 9.6 days at 1sec int., 573 days at 1 min int.



JFE Advantech Co., Ltd.



### Sensor Specifications



Model	DEFI2-L
Parameter	Photon flux density
Principle	Photodiode
Range	0~5000 $\mu\text{mol m}^{-2} \text{s}^{-1}$
Resolution	0.2 $\mu\text{mol m}^{-2} \text{s}^{-1}$
Accuracy	$\pm 4.0\%$ F.S. (0~2000 $\mu\text{mol m}^{-2} \text{s}^{-1}$ )
Depth rating	500 m depth equivalent

### Logger Specifications

Communication	Infrared to Interface Unit
Output/ transfer time	RS-232C, 115,200 bps / Approx. 22 minutes (fully recorded)
Memory medium	Internally installed flash memory 8 MB
No. of samples	Approx. 820,000 samples
A/D converter	16 bit
Measuring mode	Continuous
Measuring interval	1 to 59 s, 1 to 60 min

### Power / Dimensions



Power source	AAA alkaline battery
Consumption	Approx. 30 mA (while logging)
Material	Body: Titanium (grade 2) Window: Polycarbonate
Weight	in air 94 g, in water 61 g (including battery)
Dimensions	$\Phi 20 \text{ mm} \times 110 \text{ mm}$



### Interface Unit Specifications

Model	DEFI-IF
Communication	USB to PC (Ver2.0) / Infrared to instrument
Power	USB bus power
Operation temperature	-3 to 45 °C (no condensation)
Material	ABS resin, Acrylic resin
Dimensions	W110 mm $\times$ H66 mm $\times$ D80 mm (without cable)
Weight	225 g

\* Interface Unit is required for communication.



※ All specifications on this brochure are subject to change without notice.



**JFE Advantech Co., Ltd.**

Ocean & River Instruments Division

URL: <http://www.jfe-advantech.co.jp/>

Head Office

3-48 Takahata cho, Nishinomiya, Hyogo 663-8202

TEL. +81-798-66-1783

FAX. +81-798-66-1654

Tokyo Head Office

JFE Kuramae Bldg. 2F, 2-17-4 Kuramae, Taito ku, Tokyo 111-0051

TEL. +81-3-5825-5589

FAX. +81-3-5825-5591

Tohoku Branch

TM Bldg. 2F, 1-3-1, Ichiban cho, Aoba ku, Sendai, Miyagi 980-0811

TEL. +81-22-711-7535

FAX. +81-22-711-7534